

RESIN-GIPS PLUS

STUMPS & MODELS / STONES



FLUID STONE WITH RESIN

- MORE CONTENT IN RESIN
- BETTER RESISTANCE TO ABRASION
- ITS GREY COLOUR ALLOWS BETTER FINISHING
- VERY SMOOTH SURFACES. MAXIMUM HARDNESS



RESIN-GIPS PLUS

EXTRA HARD RESIN ADDED DIE-STONE. TYPE 4, HIGH QUALITY.

USE INSTRUCTIONS

Specially designed stone for implants. As well as for veneers, inlays and removable dies.

ADVANTAGES

New improved formula:

- · Higher resin content
- Greater resistance to abrasion

Due to the formulation with resin, you can obtain very hard and even surfaces.

Compatible with all kind of impression materials.

Controlled setting expansion which provides a good dimensional stability.

Easy to cut avoiding the formation of dust in the laboratory Very fluid gypsum: easy to use.

Exact reproducibility.

Snap setting effect.

WORKING INSTRUCTIONS

Powder/water ratio: 100 g / 20 ml Working temperature: 20-23°C Mixing: mechanical under vacuum: 30 sec.

Add the powder to the demineralised water following the recommended ratio.

SALES FORMAT

1108-062	Eco-pack 6 kg (3 x 2 kg Al bag)	Colour Grey
1108-K20	Test Pack 1 kg (1 x 2 kg Al bag)	Colour Grey



PHYSICAL CHARACTERISTICS

Working time:	7 min.
Initial setting:	8 min.
(Vicat test according to ISO 6873)	
Final setting:	10 min.
(Vicat test according to ISO 6873)	
Setting time:	30 min.
Setting expansion (2 h.):	0.10 %
Compressive strength (1 h.):	50 MPa









Tel. +34 972 526 169 Polígono Empordà Internacional 17469 . VILAMALLA (Girona) . Spain

protechno@protechno.com www.protechno.com